WOODTONE
inspired living, inside and out

REALPOST™ STRUCTURAL COLUMN

SUBMITTAL DOCUMENT

Submitted to:

Project Name:

Submitted by:

Date:

Profile:

Coating:

Texture:

REALPOST™ STRUCTURAL COLUMN

SPECIFICATION SHEET

Manufacturer
Woodtone Building Products
- *8007 Aitken Road, Chilliwack BC*
- *9403 24th Place West, Everett WA*

Features
- *Structurally certified in Canada and US*
- *Protects against warping, twisting and cracking*
- *15 year warranty against manufacturer's defect*

Structural Certifications
- *Canada: CCMC #13314-R*
- *USA: Intertek CCRR 1102*

Available Substrates
- *Comb four sides, knotty SPF*
- *Resawn four sides, knotty SPF*
- *Smooth four sides, knotty SPF*

Profiles Available
- *4x4 (3-1/2"x3-1/2")*
- *6x6 (5-1/2"x5-1/2")*
- *8x8 (7-1/4"x7-1/4")*

Use
Woodtone RealPost™ products are great for use as porch posts, on gazebos or pergolas, or as decorative posts.

Texture & Finish
Woodtone RealPost™ is created from combed or resawn knotty SPF (spruce/pine/fir). The product is coated using a proprietary Hybrid Alkyd Emulsion primer by Sherwin Williams in either gray or brown color.

Installation
Full installation guide: woodtone.com
- *Consult and follow all applicable local building codes*
- *Do not install defective material, review before install.*
- *All trimmed ends must be re-sealed prior to install.*
- *We recommend using connector products from Simpson Strong-tie, USP Structural Connectors or Tamlyn.*

Load Table
Load table is based on allowable eccentrical loads at a moisture content of 19%:

Profile	10' length	12' length
4x4	*3,467 lbs*	*2,629 lbs*
6x6	*11,638 lbs*	*9,534 lbs*
8x8	*19,894 lbs*	*17,654 lbs*

Storage and Handling
Full Care and Maintenance guide: woodtone.com
- *Do not store pallets directly on the ground*
- *Ensure that slip sheeting stays between boards*
- *Use plastic wrap provided to keep the product dry*
- *Do not lift more than 2 packs by forklift at a time*
- *Do not stack pallets more than 3 high*

Warranty
Woodtone RealPost™ carries a 15 year limited warranty against manufacturer's defects. Visit woodtone.com for full details.

Important Notes
- *RealPost™ is manufactured from knotty SPF. Finished product will not be blemish free.*
- *On site topcoat is required for warranty to remain intact.*
- *Warranty does not cover natural occurrences like extractives, knot-bleed, variations in grain and color, knots, mineral streaks and pitch pockets.*
- *Installation will be considered final acceptance of product, review material prior to installation.*

Strategic Accounts/Large Job Quotes
For assistance with commercial or multi-residential applications and large job quotes, please contact our Strategic Accounts team at spec@woodtone.com.

RealPost™ color and texture options are shown below:

COMBED 4 SIDES
GRAY PRIMER

RESAWN 4 SIDES
GRAY PRIMER

SMOOTH 4 SIDES
GRAY PRIMER

RESAWN 4 SIDES
CEDARTONE

RESAWN 4 SIDES
BROWN PRIMER

Note: RealPost™ products are manufactured from a knotty SPF. If a blemish free appearance is desired, we recommend putty to fill any natural imperfections and a solid top coat to finish the look. On site topcoat is required for the warranty to remain intact.